

DURALITE MULE – SPEC SHEET



OVERVIEW:

The Duralite Mule is constructed from only the best quality materials and is designed to be rugged and agile. All aspects of the Mule have been designed to ensure maximum safety for the user(s). It is constructed of mainly steel components and is capable of carrying, winching and towing your rods, tooling and any other equipment that you may need on the jobsite.

Performance:		Winch:	
Maximum incline angle	30°	2 x M15000 Warn Winches	
Maximum Track Speed	1 MPH / 1.6 KPH	CABLE CAPACITY:	7/16" (11 MM): 90' (27 M)
Standard Engines:		PULL CAPACITY:	15,000 LBS/6,804 KG
1 – Kubota Diesel 40HP @ 2,500 RPM			

Hydraulic Module:

Our proven hydraulic system is an open center, vented tank system, constructed using only top brand name pumps, valves, and accessories. This hydraulic system delivers 14 GPM at 2,500 RPM.

Dimensions & Weights:

Overall Width:	47" (1.19 M)
Overall Length:	125.25" (3.18 M)
Total Weight (Wet):	4,400 lbs / 1,996kg

Capacity:

Fuel Capacity	16 US Gallons / 60 Liters
Hydraulic Tank Capacity	16 US Gallons / 60 Liters
Total Carrying Capacity	3,600 lbs / 1,633 kg
Rod Carrying Capacity	126 Meters NQ (42 Rods)



Duralite Diamond Drills is constantly improving its products and must therefore reserve the right to change materials, weights, specifications, and design without notice.