

DURALITE MINIROCK – SPEC SHEET



OVERVIEW:

The Duralite MiniRock is constructed from only the best quality materials and is designed to be rugged and agile. All aspects of the MiniRock have been designed to ensure maximum safety for the user(s). It is constructed of mainly steel components and is capable of carrying & moving any material that you may need on the jobsite.

<u>Performance:</u> Maximum incline angle 30° Maximum Track Speed 1 MPH / 1.6 KPH.	<u>Dump Capacity:</u> <u>VOLUME:</u> 88.5 CU FEET / 2.5 CU METRES <u>WEIGHT CAPACITY:</u> 4,000 LBS / 1,814 KG
<u>Standard Engine:</u> 1 – Kubota Diesel 40HP @ 2,500 RPM	<u>Drivetrain:</u> Rubber track drives with wireless remote control

Hydraulic Module:

Our proven hydraulic system is an open center, vented tank system, constructed using only top brand name pumps, valves, and accessories. This hydraulic system delivers 14 GPM at 2,500 RPM.

Dimensions & Weights:

Overall Width:	61" (1.55 M)
Overall Length:	132" (3.35 M)
Total Weight (Wet):	4,550 lbs / 2,064 kg

Fluid Capacity:

Fuel Capacity	16 US Gallons / 60 Liters
Hydraulic Tank Capacity	16 US Gallons / 60 Liters

